

AGM BATTERY NEW ORANGE SERIES



Typical Application

- > Telecommunication equipment
- > Electronic instruments
- > Fire alarm
- > Security Devices
- > UPS power supply
- > Emergency lighting
- > Solar Application

INV Series:

Voltage: 2V, 4V, 6V, 12V,

Capacity: 0.4AH to 3000AH

Designed Service Life: 10-12 years

(Designed floating service life at 20 °C/68 °F)

General Features:

- > Non-spillable
- > Sealed and maintenance-free operation
- > High Quality and High Reliability
- > Exceptional deep discharge recovery
- > Low self-discharge
- > Long Service Life
- > Solid Copper Terminals
- > Tank-formed Plates
- > Computer-aided Design and Manufacturing
- > 30% DOD 1150 cycles
- > 60% DOD 650 cycles
- > Deep cycles Series

No.	Model No.	Volts	Capacity (Ah) 20 HR	Appx. Dimension(mm)				Terminals	Approx. Weight (KG)	Q'ty/ CTN	Meas		
				L±2	W±2	H±2	TH±2				L	W	H
1	INV	6	4.0	70	48	100	106	F1	0.72	20	29.5	24.5	12.6
2	INV	6	4.5	70	48	100	106	F1	0.82	20	29.5	24.5	12.6
3	INV	6	7.0	151	35	94	100	F1	1.23	16	31.2	29.0	12.2
4	INV	6	10	151	55	94	100	F1	1.65	10	31.0	26.0	12.3
5	INV	12	3.3	134	67	61	67	F1	1.35	10	34.5	27.8	8.80
6	INV	12	5.0	90	70	102	108	F1	1.74	10	36.0	19.0	12.8
7	INV	12	7.0	151	65	94	100	F1	2.09	10	34.0	31.0	12.8
8	INV	12	7.5	151	65	94	100	F2	2.19	10	34.0	31.0	12.8
9	INV	12	9.0	151	65	94	100	F2	2.39	10	34.0	31.0	12.8
10	INV	12	12	151	98	96	100	F2	3.54	4	31.3	20.5	12.5
11	INV	12	20	181	77	167	167	L1	5.22	4	31.5	19.0	19.0
12	INV	12	24	174	166	125	125	T0/L2	7.50	2	35.6	20.2	18.0
13	INV	12	26	174	166	125	125	T0/L2	8.05	2	35.6	20.2	18.0
14	INV	12	38	196	166	176	176	T1	13.05	2	35.5	22.0	23.0
15	INV	12	40	196	166	176	180	B1	13.05	2	35.5	22.0	23.0